

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions and listings of claims in the application:

1. (Currently Amended) A method of accessing an information system using a portable access device, the method comprising:

identifying a communication ~~protocol~~profile associated with a first network server;

attempting, by the portable access device, to establish a communication link between the portable access device and the first network server using communication medium that is selected by the portable access device based on the communication ~~protocol~~profile and a location of the portable access device with respect to the first network server, wherein the communication medium is selected from the group consisting of: a local wireless LAN, a remote wireless LAN, a wireline LAN, and a Public Switched Telephone Network (PSTN); and

capturing data received by the portable access device in a memory located in the portable access device in accordance with a failed attempt to establish the communication link.

2. (Currently Amended) The method of claim 1 wherein said step of identifying a communication ~~protocol~~profile associated with said network server further comprises the following steps:

searching an internal database for a communication ~~protocol~~profile associated with the first network server; and

retrieving said communication ~~protocol~~profile from the internal database.

3. (Currently Amended) A method of accessing an information system using a portable access device, the method comprising:

identifying, by the portable access device, a communication ~~protocol~~profile associated with a first network server, wherein the identifying a comprises:

searching an internal database for the communication ~~protocol~~profile;

transmitting from the portable access device to a second network server, a request to access the first network server when the communication ~~protocol~~profile cannot be found in the internal database; and

retrieving the communication ~~protocol~~profile from the second network server;

attempting, by the portable access device, to establish a communication link between the portable access device and the first network server using one of a plurality of communication media, in accordance with the communication ~~protocol~~profile, wherein the one of a plurality of communication media is selected from the group consisting of: a local wireless LAN, a remote wireless LAN, a wireline LAN, and a Public Switched Telephone Network (PSTN); and capturing data in a memory location in accordance with a failed attempt to establish the communication link.

4. (Previously Presented) The method of claim 3 wherein transmitting a request from the portable access device to the second network server comprises:

transmitting a signal from the portable access device to a local wireless LAN transceiver;

transmitting a second signal from the portable access device to a remove wireless transceiver when a communication link cannot be established with the local wireless LAN transceiver; and

connecting the portable access device to a public switched telephone network (PSTN) when a communication link cannot be established with the remove wireless transceiver.

5. (Currently Amended) The method of claim 1 wherein said step of attempting to establish a communication link with said first network server is further comprised of the following steps:

configuring said portable access device to transmit using one of a plurality of communication media, in accordance with said communication ~~protocol~~ profile;

verifying the availability of said communication medium; and

initiating communication between said portable access device and said network server along said communication medium.

6. (Previously Presented) The method of claim 1 wherein attempting to establish a communication link server comprises:

transmitting a signal from said portable access device to a local wireless LAN transceiver;

transmitting a second signal from said portable access device to a remote wireless transceiver when a communication link cannot be established with said local wireless LAN transceiver; and

requesting a connection to a PSTN when a communication link cannot be established with said remote wireless transceiver.

7. (Currently Amended) A method of accessing an information system using a portable access device, the method comprising:

receiving a request from said portable access device to access a network server;

identifying a communication ~~protocol~~profile associated with said network server;

transmitting said communication ~~protocol~~profile to said portable access device;

and

establishing a communication link between said portable access device and said network server using a communication medium that is selected based on said communication ~~protocol~~profile and a location of said portable access device with respect to said network server, wherein said communication medium is selected from the group consisting of: local wireless LAN, remote wireless LAN, wireline LAN, and Public Switched Telephone Network (PSTN).

8. (Original) The method of claim 7 further comprising the step of configuring said portable access device to capture data in memory in accordance with a failed attempt to establish said communication link.

9. (Currently Amended) The method of claim 7 wherein said step of identifying a communication ~~protocol~~profile associated with said network device further comprises the following steps:

accessing a central database;

searching said central database for a communication ~~protocol~~profile associated with said network server; and

retrieving said communication ~~protocol~~profile.

10. (Currently Amended) The method of claim 7 wherein said step of establishing communication between said portable access device and said network server is further comprised of the following steps:

configuring said portable access device to transmit using one of a plurality of communication media in accordance with said communication ~~protocol~~profile;

verifying the availability of said communication medium; and

initiating communication between said portable access device and said network server using one of said communication media.

11. (Previously Presented) The method of claim 7 wherein establishing a communication link comprises:

transmitting a signal to a local wireless LAN transceiver;

transmitting a second signal to a remote wireless transceiver when a communication link cannot be established with said local wireless LAN transceiver; and

connecting to a PSTN when a communication link cannot be established with said remote wireless transceiver.

12. (Currently Amended) A method of access an information system using a portable access device, the method comprising:

transmitting from said portable access device to a first network server, a request to access a second network server;

receiving said request at said first network server;

identifying a communication ~~protocol~~profile associated with said second network server;

transmitting said communication ~~protocol~~profile from said first network server to said portable access device; and

establishing a communication link between said portable access device and said second network server using a communication medium that is selected based on said communication ~~protocol~~profile and a location of said portable access device with respect to said second network server, wherein said communication medium is selected from the group consisting of: local wireless LAN, remote wireless LAN, wireline LAN, and Public Switched Telephone Network (PSTN).

13. (Original) The method of claim 12 further comprising the step of configuring said portable access device to capture data in memory in accordance with a failed attempt to establish said communication link.

14. (Original) The method of claim 12 wherein said step of transmitting from a portable access device to a first network server is further comprised of the following steps:

transmitting a signal from a portable access device to a local wireless LAN transceiver;

transmitting a second signal from said portable access device to a remote wireless transceiver when a communication link cannot be established with said local wireless LAN transceiver; and

connecting said portable access device to a public switched telephone network (PSTN) when a communication link cannot be established with said remote wireless transceiver.

15. (Currently Amended) The method of claim 12 wherein identifying a communication ~~protocol~~profile further comprises:

accessing a central database; and

retrieving a communication ~~protocol~~profile that corresponds to said second network server.

16. (Currently Amended) The method of claim 12 wherein establishing a communication link comprises:

configuring said portable access device to transmit using one of a plurality of communication media in accordance with said communication ~~protocol~~profile;

verifying the availability of a communication medium; and

initiating communication between said portable access device and said second network server along said communication medium.

17. (Previously Presented) The method of claim 12 wherein establishing a communication link comprises:

transmitting a signal to a local wireless LAN transceiver;

transmitting a second signal to a remote wireless transceiver when a communication link cannot be established with said local wireless LAN transceiver; and

connecting to a PSTN when a communication link cannot be established with said remote wireless transceiver.

18-29. (Canceled)

30. (Currently Amended) A computer-readable medium containing instructions for accessing an information system comprising a portable access device and a plurality of network servers, the method comprising:

identifying a communication ~~protocol~~profile associated with a first network server;

attempting, by the portable access device, to establish a communication link between the portable access device and the first network server using a communication medium that is selected by the portable access device based on the communication ~~protocol~~profile and a location of the portable access device with respect to the first network server, wherein communication medium is selected from the group consisting



of: a local wireless LAN, a remote wireless LAN, a wireline LAN, and a Public Switched Telephone Network (PSTN); and

capturing data received by the portable access device in a memory located in the portable access device in accordance with a failed attempt to establish the communication link.

31. (Currently Amended) The computer-readable medium of claim 30 wherein said step of identifying a communication ~~protocol~~profile associated with said network server further comprises the following steps:

searching an internal database for a communication ~~protocol~~profile associated with the first network server; and

retrieving said communication ~~protocol~~profile from the internal database.

32. (Currently Amended) A computer-readable medium containing instructions for accessing an information system comprising a portable access device and a plurality of network servers, the method comprising:

identifying, by the portable access device, a communication ~~protocol~~profile associated with a first network server, wherein identifying a communication ~~protocol~~profile further comprises:

searching an internal database for the communication ~~protocol~~profile  
transmitting from the portable access device to a second network server, a request to access said first network server when said communication ~~protocol~~profile cannot be found in said internal database; and

retrieving the communication ~~protocol~~profile from said second network server;  
attempting, by the portable access device, to establish a communication link  
between the portable access device and the first network server using one of a plurality  
of communication media, in accordance with the communication ~~protocol~~profile,  
wherein the one of a plurality of communication media is selected from the group  
consisting of: a local wireless LAN, a remote wireless LAN, a wireline LAN, and a Public  
Switched Telephone Network (PSTN); and  
capturing data in a memory location in accordance with a failed attempt to  
establish the communication link.

33. (Previously Presented) The computer-readable medium of claim 32  
wherein transmitting a request from the portable access device to the second network  
server comprises:

transmitting a signal from the portable access device to a local wireless LAN  
transceiver;

transmitting a second signal the portable access device to a remote wireless  
transceiver when a communication link cannot be established with the local wireless  
LAN transceiver; and

connecting the portable access device to a PSTN when a communication link  
cannot be established with the remote wireless transceiver.

34. (Currently Amended) The computer-readable medium of claim 30 wherein said step of attempting to establish a communication link with said first network server is further comprised of the following steps:

configuring said portable access device to transmit using one of a plurality of communication media, in accordance with said communication ~~profile~~ profile;

verifying the availability of said communication medium; and

initiating communication between said portable access device and said first network server along said communication medium.

35. (Previously Presented) The computer-readable medium of claim 30 wherein attempting to establish a communication link comprises:

transmitting a signal from said portable access device to a local wireless LAN transceiver;

transmitting a second signal from said portable access device to a remote wireless transceiver when a communication link cannot be established with said local wireless LAN transceiver; and

requesting a connection to a PSTN when a communication link cannot be established with said remote wireless transceiver.

36. (Currently Amended) A computer-readable medium containing instructions for accessing an information system comprising an access device and a plurality of network servers, the method comprising:

receiving a request from a portable access device to access a network server;

identifying a communication ~~protocol~~profile associated with said network server;  
transmitting said communication ~~protocol~~profile to said portable access device;  
and

establishing a communication link between said portable access device and said network server using a plurality of communication medium that is selected based on said communication ~~protocol~~profile and a location of said portable access device with respect to said network server, wherein said communication medium is selected from the group consisting of: local wireless LAN, remote wireless LAN, wireline LAN, and Public Switched Telephone Network (PSTN).

37. (Original) The computer-readable medium of claim 36 further comprising the step of configuring said portable access device to capture data in memory in accordance with a failed attempt to establish said communication link.

38. (Currently Amended) The computer-readable medium of claim 36 wherein said step of identifying a communication ~~protocol~~profile associated with said network device further comprises the following steps:

accessing a central database;  
searching said central database for a communication ~~protocol~~profile associated with said network server; and  
retrieving said communication ~~protocol~~profile.

39. (Currently Amended) The computer-readable medium of claim 36 wherein said step of establishing communication between said portable access device and said network server is further comprises of the following steps:

configuring said portable access device to transmit using one of a plurality of communication media in accordance with said communication ~~protocol~~ profile;

verifying the availability of said communication medium; and

initiating communication between said portable access device and said network server using one of said communication media.

40. (Previously Presented) The computer-readable medium of claim 36 wherein establishing communication comprises:

transmitting a signal to a local wireless LAN transceiver;

transmitting a second signal to a remote wireless transceiver when a communication link cannot be established with said local wireless LAN transceiver; and

connecting to a PSTN when a communication link cannot be established with said remote wireless transceiver.

41. (Currently Amended) A computer-readable medium containing instructions for accessing an information system comprising an access device and a plurality of network servers, the method comprising:

transmitting from a portable access device to a first network server, a request to access a second network server;

receiving said request at said first network server;

identifying a communication ~~protocol~~profile associated with said second network server;

transmitting said communication ~~protocol~~profile to said portable access device;  
and

establishing a communication link between said portable access device and said second network server using a communication medium that is selected based on said communication ~~protocol~~profile and a location of the portable access device with respect to said second network server.

42. (Original) The computer-readable medium of claim 41 further comprising the step of configuring said portable access device to capture data in memory in accordance with a failed attempt to establish said communication link.

43. (Original) The computer-readable medium of claim 41 wherein said step of transmitting from a portable access device to a first network server is further comprised of the following steps:

transmitting a signal from a portable access device to a local wireless LAN transceiver;

transmitting a second signal from said portable access device to a remote wireless transceiver when a communication link cannot be established with said local wireless LAN transceiver; and

connecting said portable access device to a PSTN when a communication link cannot be established with said remote wireless transceiver.

44. (Currently Amended) The computer-readable medium of claim 41 wherein identifying a communication ~~protocol~~profile further comprises:

- accessing a central database; and
- retrieving a communication ~~protocol~~profile that corresponds to said second network server.

45. (Currently Amended) The computer-readable medium of claim 41 wherein establishing a communication link comprises:

- configuring said portable access device to transmit using one of a plurality of communication media in accordance with said communication ~~protocol~~profile;
- verifying the availability of a communication medium; and
- initiating communication between said ~~protocol~~profile access device and said second network server along said communication medium.

46. (Previously Presented) The computer-readable medium of claim 41 wherein establishing a communication link comprises:

- transmitting a signal to a local wireless LAN transceiver;
- transmitting a second signal to a remote wireless transceiver when a communication link cannot be established with said local wireless LAN transceiver; and
- connecting to a PSTN when a communication link cannot be established with said remote wireless transceiver.

47. (Currently Amended) The method of claim 1 wherein the identifying comprises:

searching an internal database of the portable access device for the communication ~~protocol~~profile associated with the first network server;

transmitting from the portable access device to a second network server, a request to access the first network server when the communication ~~protocol~~profile cannot be found in the internal database; and

retrieving the communication ~~protocol~~profile server from the second network server.

48. (Previously Presented) The method of claim 47 wherein transmitting a request from the portable access device to the second network server comprises:

transmitting a signal from the portable access device to a local wireless LAN transceiver;

transmitting a second signal from the portable access device to a remote wireless transceiver when a communication link cannot be established with the local wireless LAN transceiver; and

connecting the portable access device to a public switched telephone network (PSTN) when a communication link cannot be established with the remote wireless transceiver.

49. (Currently Amended) The computer-readable medium of claim 30 wherein identifying a communication ~~protocol~~profile further comprises:



searching an internal database of the portable access device for the communication ~~protocol~~ profile;

transmitting from the portable access device to a second network server, a request to access the first network server when the communication ~~protocol~~ profile cannot be found in the internal database; and

retrieving the communication ~~protocol~~ profile from the second network server.

50. (Previously Presented) The computer-readable medium of claim 49 wherein transmitting a request from a portable access device to the second network server comprises:

transmitting a signal from the portable access device to a local wireless LAN transceiver;

transmitting a second signal from the portable access device to a remote wireless transceiver when a communication link cannot be established with the local wireless LAN transceiver; and

connecting the portable access device to a PSTN when a communication link cannot be established with the remote wireless transceiver.

51. (Currently Amended) A method of accessing information using an access device, the method comprising:

identifying, by the access device, a communication ~~protocol~~ profile associated with a first server;

attempting, by the access device, to establish a communication link between the access device and the first server, in accordance with the communication ~~protocol~~ profile, wherein the attempting includes initiating a first attempt to establish communication with the first server via a local wireless network, initiating a second attempt to establish communication via a remote wireless network if the first attempt fails, and initiating a third attempt to establish communication via a public switched telephone network if the second attempt fails; and

accessing the information from the first server when the communication link is established.

52. (Currently Amended) The method of claim 51, wherein identifying a communication ~~protocol~~ profile comprises:

determining, by the access device, whether or not the communication ~~protocol~~ profile is stored locally by the access device; and

establishing communication with a second server to retrieve the communication ~~protocol~~ profile, if the communication ~~protocol~~ profile is not stored locally.

53. (Previously Presented) The method of claim 52, wherein establishing communication with the second server comprises:

initiating a first attempt to establish communication via a local wireless network, initiating a second attempt to establish communication via a remote wireless network if the first attempt fails, and initiating a third attempt to establish communication via a public switched telephone network if the second attempt fails.

54. (Previously Presented) The method of claim 51, further comprising:  
configuring the access device to operate in a local capture mode such that data  
received by the access device is stored in a memory located in the access device, if the  
third attempt fails.